

SL SERIES

The SL 2 subcompact vacuum lifting system is the ultimate attachment—lightweight and extremely versatile, the system has been updated with an improved hydraulic system and modular pads to work with more machines and for more applications! Featuring all-aluminum construction, the patent pending design runs off the host machine’s hydraulic system and can be easily attached in minutes to lift steel plate, saw-cut concrete, granite and marble slabs, landscape pavers and more! In addition, quick-connect hydraulic hoses make switching between attachments fast and easy so you can maximize productivity on the job. Perfect for floor, sidewalk, driveway, road and landscaping projects.

- Available with manual or wireless remote control.
- Connects to small excavators, backhoes and cranes using clevis hook connection.
- Designed to lift concrete, marble, granite, metal, steel, iron and landscape pavers.
- All system components are fabricated from high quality aluminum to maximize overall lifting capacity of the host machine.
- Universal mounting plates allow easy attachment to all skid steer models.
- Includes quick-connect hydraulic hoses and factory pre-set flow control valve to ensure optimal performance.
- Hydraulically driven vacuum pump operates using the auxiliary hydraulics from the host machine (minimum 10 GPM required with maximum 3,000 PSI).
- Models with innovative accumulator design allow contractors to use the system on equipment without a case drain.



Specifications

	Lift Capacity (kg)	Weight (kg)	LxWxH (mm)
SL2	4,400 lb (2 tonne)	125 lb (57 kg)	L 23" (584 mm) x H 25" (635 mm) x W 29" (737 mm)

STANDARD PAD OPTIONS

	Lift Capacity (kg)	Weight (kg)	LxWxH (mm)
SL2-0832	1,586 lb (719 kg)	19.3 lb (8.7 kg)	8" x 32" (203x813 mm) inner/12" x 36" (305x914 mm) outer
SL2-1236	2,409 lb (1,093 kg)	24.1 lb (11 kg)	12" x 36" (305x914 mm) inner/16" x 40" (406x1016 mm) outer
SL2-2424	3,467 lb (1,573 kg)	33.7 lb (15.2 kg)	24" x 24" (610x610 mm) inner/28" x 28" (711x711 mm) outer

Parts & Accessories

PT3000-700A	HLOK Tough Seal™, 10 ft (3 m)	PT7600-025A	SL/CM Battery Charger
PT7401-002	SL/CM Vacuum Filter Element	PT8300-400A	PS/SL Mounting Assembly for Mini Skid Steer (top mount)
PT7600-100	SL/CM 12V Rechargeable Battery	PT8300-500A	SL/CM Mounting Assembly for Mini Skid Steer (side mount)